

REM-10



(E3/L3) HAULAGE/ARTICULATED TIRE

The OEM Certified REM-10 OTR tire features a multi-function, non-directional tread design for optimum performance. Designed for the rugged needs of articulating trucks, the REM-10 OTR is built with a unique center block tread design, that delivers superior off-the-road traction, and a smooth ride in all types of terrain.

| PRODUCT CODE | TIRE SIZE | PATTERN | LOAD SYMBOL | SPEED MAX (KM/H) | SPEED MAX (MPH) | OVERALL DIAMETER (INCH) | SECTION WIDTH (INCH) | TREAD DEPTH (32NDS) | RIM | SINGLE MAX LOAD/PRESSURE | TIRE WEIGHT | TIRE TYPE | NOTE |
|--------------|-----------|---------|-------------|------------------|-----------------|-------------------------|----------------------|---------------------|-----------|--------------------------|--------------|-----------|------|
| 1087106252 | 26.5R25 | REM-10 | ★★ | 50 | 30 | 69 | 27 | 51 | 22.00/3.0 | 25300lb/76psi | 463kg/1023lb | T/L | - |
| 1087106252 | 26.5R25 | REM-10 | ★★ | 10 | 5 | 69 | 27 | 51 | 22.00/3.0 | 40700lb/94psi | 463kg/1023lb | T/L | - |
| 1087102955 | 29.5R25 | REM-10 | ★★ | 50 | 30 | 74 | 29 | 55 | 25.00/3.5 | 30800lb/76psi | 597kg/1285lb | T/L | - |
| 1087102955 | 29.5R25 | REM-10 | ★★ | 10 | 5 | 74 | 29 | 55 | 25.00/3.5 | 49280lb/94psi | 597kg/1285lb | T/L | - |