

Features

- Extra-deep, open lug L5 traction pattern combines excellent traction and high resistance to wear and cutting.
- Specifically designed to maximize service life in the harshest applications.

MPVS5



Size	Rating	Type	Rim	O.D.	S.W	T.D.	Inf. P.	L.C.C. (1bs/kg)	L.I.
				in	in	32nds	psi	5 mph	
				mm	mm	mm	KPa	10 kph	
17.5R25	★★	TL	14.00/1.5	55.4	17.0	80	94	18700	182A2
17.5R25	★★	TL	14.00/1.5	1408	443	64	650	8500	182A2
20.5R25	★★	TL	17.00/2.0	60.9	20.9	91	94	25400	193A2
23.5R25	★★	TL	17.00/2.0	1547	532	72	650	11500	193A2
23.5R25	★★	TL	19.50/2.5	65.7	24.0	102	94	32000	201A2
23.5R25	★★	TL	19.50/2.5	1668	610	81	650	14500	201A2
26.5R25	★★	TL	22.00/3.0	70.7	26.6	109	94	40800	209A2
26.5R25	★★	TL	22.00/3.0	1796	675	87	650	18500	209A2
29.5R25	★★	TL	25.00/3.5	75.2	30.4	117	94	49400	216A2
29.5R25	★★	TL	25.00/3.5	1910	772	93	650	22400	216A2
29.5R29	★★	TL	25.00/3.5	78.5	30.8	117	94	52000	218A2
29.5R29	★★	TL	25.00/3.5	1995	782	93	650	23600	218A2
875/65R29	★★	TL	27.00/3.5	75.6	33.8	114	91	56800	221A2
875/65R29	★★	TL	27.00/3.5	1920	859	91	625	25750	221A2